

# efka® - 3033

**Additive designed to improve levelling and to increase substrate wetting, scratch and abrasion resistance**

---

**Composition:** Organically modified polysiloxane

---

**Data:**

Active ingredients	: 14 - 16%	
Solvent	: butylacetate	
Density at 20 °C	: 0.90 - 0.92 g/cm <sup>3</sup>	DIN 51757
Refractive index	: 1.400 - 1.410	DIN 53491
Flashpoint	: 24 °C	ISO 3679
Colour	: max. 1	ISO 4630
Appearance	: clear liquid	

---

**Properties:** EFKA-3033 is a very effective additive, which increases slip and surface smoothness.  
It has excellent compatibility properties, making it very suitable for use in clear coatings.  
EFKA-3033:

- improves levelling
- increases scratch and abrasion resistance
- prevents floating
- enhances anti-blocking characteristics
- prevents cratering

---

**Application:** EFKA-3033 is recommended for all kinds of solvent-based coatings.

---

**Addition:** 0.1 - 1.0% on total formulation

---

**Incorporation:** EFKA-3033 can be added at any stage during the production process. If added during the dispersion process, it speeds up wetting.

---

**Storage:** EFKA-3033 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container.

---

**Packaging:** 25 kg and 180 kg non-returnable containers

---