

# efka® - 3232

**Additive designed to improve levelling and to increase substrate wetting, scratch and abrasion resistance**

---

**Composition:** Organically modified polysiloxane

---

**Data:**

Active ingredients	: 100%	
Density at 20 °C	: 1.06 - 1.08 g/cm <sup>3</sup>	DIN 51757
Refractive index	: 1.440 - 1.460	DIN 53491
Flashpoint	: > 100 °C	ISO 3679
Colour	: max. 2	ISO 4630

---

**Properties:** EFKA-3232 is a very effective additive, which increases slip and surface smoothness. It has excellent compatibility properties, making it very suitable for use in clear coatings.

EFKA-3232:

- improves levelling
  - increases scratch and abrasion resistance
  - prevents floating
  - improves anti-blocking characteristics
  - prevents cratering
- 

**Application:** EFKA-3232 is recommended for all kinds of solvent-based coatings.

---

**Addition:** 0.1 - 0.2% on total formulation

---

**Incorporation:** EFKA-3232 can be added at any stage during the production process. If added during the dispersion process, it speeds up wetting.

---

**Storage:** EFKA-3232 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container.

---

**Packaging:** 25 kg and 180 kg non-returnable containers

---